

# MastaCove45

## CORNICE CEMENT



## TECH DATA

**MastaCove45** is a plaster based cornice cement used to attach cornice and decorative features to walls and ceilings. It has a consistent working time of 30 minutes with a 45 minute setting time, to suit all cornice applications, from paper faced and fibrous cornice to polishing mitres for smooth painting surfaces.



### Performance

#### Mixing

Mixes easily to a creamy gauge.

#### Body and Grab

Good body for easy placement when buttering cornice, great initial grab and easy to reposition cornice.

#### Workback

Partially set product can be reworked and used again to deliver the high finish required for polishing mitres. Easy to straight stop and clean.

#### Setting

An even and gradual 45 minute set which can be accelerated by extended mixing, either by hand on the hawk or by drill mix. Flexible product setting meets the different needs of every project. This allows plenty of time for cutting and polishing mitres.

#### Sustainable

Low VOC meeting sustainable building project requirements.

### Benefits

- > Mixes easily to a creamy gauge
- > Sets evenly
- > Excellent workback

### Product Information

SIZE	20kg paper bag	
TYPE	Setting powder cement	
MIXING RATIO	1L of water to 2kg of MastaCove45	
WORKING TIME	30 – 45 minutes	
SETTING TIME	45 minutes	<input checked="" type="checkbox"/> Adjustable
SYSTEM USAGE	<input checked="" type="checkbox"/> Cornice	<input checked="" type="checkbox"/> Patching
	<input checked="" type="checkbox"/> Standard systems	<input checked="" type="checkbox"/> Wet area systems
VOC	<50g/L as VOC content per coating	

# MastaCove45

## CORNICE CEMENT

# KNAUF

## TECH DATA

### Application

- Always use clean tools and containers.
- Pour the required amount of clean tap water into a container. Add the powder into water, mixing continuously to a smooth, thick consistency. Soaking is not recommended.
- Only mix enough cement to be used in 30 minutes and do not contaminate with previously mixed batches. Once the material starts to set it cannot be remixed.
- MastaCove45 will accept most types of decorative finishes. In accordance with AS/NZS 2311 *Guide to the painting of buildings*, a three coat paint system must be used. This consists of a sealer/undercoat and two coats of paint.

### Optimise product performance by:

- Storing in a dry, well ventilated environment fully protected from the weather.
- Washing tools before product dries and hardens.
- Ensuring MastaCove45 does not dry out before setting has taken place under severe hot dry conditions.



Quality  
ISO 9001

SAIGLOBAL

Knauf products manufactured in Australia are produced in accordance with quality systems certified as complying with AS/NZS ISO 9001:2008.

### Warranty

Knauf's products are guaranteed by a 10 Year Warranty. Visit [knaufplasterboard.com.au](http://knaufplasterboard.com.au) for details.

### Technical Advice

For technical advice, please call Knauf technical services on **1300 724 505**.