

MastaCove75

CORNICE CEMENT



TECH DATA

MastaCove75 is a plaster based cornice cement used to attach cornice and decorative features to walls and ceilings. With an extended working time of 75 minutes, it is ideal for use on large projects where more cornice can be placed from just one gauge, saving time and money.



Performance

Mixing

Mixes easily by hand or electric mixer to a smooth, creamy gauge.

Body and Grab

Good body and great initial grab. Easy to reposition cornice.

Workback

Partially set product can be reworked and used again to deliver a polished finish for mitres. Easy to straight stop and clean.

Setting

An even and gradual 75 minute set which will not be accelerated by extra mixing either by drill or by hand on the hawk. This allows plenty of time for cutting and polishing mitres.

Sustainable

Low VOC meeting sustainable building project requirements.

Benefits

- > Mixes easily to a creamy gauge
- > Stabilised set
- > Extended working time

Product Information

SIZE	20kg paper bag	
TYPE	Setting powder cement	
MIXING RATIO	1L of water to 2kg of MastaCove75	
WORKING TIME	65 – 75 minutes	
SETTING TIME	75 minutes	
SYSTEM USAGE	<input checked="" type="checkbox"/> Cornice	<input checked="" type="checkbox"/> Patching
	<input checked="" type="checkbox"/> Standard systems	<input checked="" type="checkbox"/> Wet area systems
VOC	<50g/L as VOC content per coating	

MastaCove75

CORNICE CEMENT

KNAUF

TECH DATA

Application

- Always use clean tools and containers.
- Pour the required amount of clean tap water into a container. Add the powder into water, mixing continuously to a smooth, thick consistency. Soaking is not recommended.
- Only mix enough cement to be used in 65 minutes and do not contaminate with previously mixed batches. Once the material starts to set it cannot be remixed.
- MastaCove75 will accept most types of decorative finishes. In accordance with AS/NZS 2311 *Guide to the painting of buildings*, a three coat paint system must be used. This consists of a sealer/undercoat and two coats of paint.

Optimise product performance by:

- Storing in a dry, well ventilated environment fully protected from the weather.
- Washing tools before product dries and hardens.
- Ensuring MastaCove75 does not dry out before setting has taken place under severe hot dry conditions.



Quality
ISO 9001

SAI GLOBAL

Knauf products manufactured in Australia are produced in accordance with quality systems certified as complying with AS/NZS ISO 9001:2008.

Warranty

Knauf's products are guaranteed by a 10 Year Warranty. Visit knaufplasterboard.com.au for details.

Technical Advice

For technical advice, please call Knauf technical services on **1300 724 505**.